

# Rotary Hammer XGT®

## HR005G

40Vmax • SDS-MAX • 40 mm • 8.0 J

Two-mode, anti-vibration rotary hammer for professionals

An efficient tool for SDS-MAX bits with AVT (anti-vibration technology) 40V max XGT batteries provide a high voltage. For impact and unstressed drilling and chipping. Speed range of 0 – 500 min<sup>-1</sup>. Impact energy of 8.0 J, max. Capacity of 40 mm in concrete.



### Technical specifications

Brushless Motor	✓
Nominal Battery Voltage	40 V
Battery protection	✓
No load speed	250 - 500 min <sup>-1</sup>
Impacts per Minute (IPM)	1450 - 2900 min <sup>-1</sup>
Max. Drilling Diameter in Concrete	40 mm
Optimum Drilling Diameter Range in Concrete	16 - 30 mm
Impact Energy	8 J
Drilling diameter with TCT core bit	105 mm
Plastic Carrying Case	✓
Sound Power Level (L <sub>WA</sub> )	101 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	90 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes), Impact Drilling	4,6 m/s <sup>2</sup>

### User benefits

- Soft start for smooth start-ups
- Anti-Vibration Technology (AVT) for extremely low vibration
- Twin LED job light with pre-glow and afterglow functions illuminates the work area
- Auto-start Wireless System (AWS) connects to vacuum cleaner with Bluetooth
- Active Feedback sensing Technology (AFT) turns the motor off if bit rotation is suddenly forced to stop
- Brushless motor eliminates carbon brushes, enabling the Brushless motor to run cooler and more efficiently for longer life
- Battery protection circuit protects against overloading, over-discharging and over-heating

Link to product - [www.makita.com](http://www.makita.com)



# Related products

## Optional AC

**123138-5**

Straight Side Handle



**181490-7**

Grease for SDS Drills and Hammers



**198993-4**

Grease vessel for bit 100 ml



**331955-1**

Depth Gauge



**821837-0**

Plastic Case



**BL4025**

Battery XGT® 2,5 Ah



**BL4040**

Battery XGT® 4,0 Ah



---

## Other

[User manual](#)

[Parts drawing](#)